

Gages for Concrete KM & KMC



Patterns, Gage Resistance, Gage Factor	Models	Dimensions (mm)				Remarks
		Grid		Base		
		Length	Width	Length	Width	

●KM Series Embedded Strain Gages

When ordering, suffix the lead-wire cable code (See table at the right) to the model number with a space in between.

E.g.

KM-120-120-H2-11 W5M3

for the gage with a vinyl-coated flat 3-wire cable 5 m long

Uniaxial foil strain gages with vinyl-coated flat 2-wire cable

Resistance: 120 Ω

Gage factor: Approx. 1.8



The KM series gages are designed to be embedded in mortar or concrete for the purpose of measuring the internal stress. To ensure better adhesion to mortar or the like, the KM series gages feature a specially treated surface. They also provide suitable waterproofness and elastic modulus for the intended purpose.

Operating Temperature Range -10 to 70°C

■Types, lengths and codes of lead-wire cables pre-attached to KM gages

Types Length	KM-30 Vinyl-coated flat 2-wire cable	KM-120 Vinyl-coated flat 3-wire cable
	H1	H2
1 m	Y1M2	W1M3
3 m	Y3M2	W3M3
5 m	Y5M2	W5M3
Operating temp.	-10 to 70°C	

*For other lead-wire cable lengths, contact us.

The following model with the lead-wire cable code Y1M2 is delivered with a vinyl-coated flat 2-wire cable 1 m long pre-attached.

KM-30-120-H1-11 Y1M2

30×9×3

1 gage/ pkg

Uniaxial foil strain gages with vinyl-coated flat 3-wire cable

Resistance: 120 Ω

Gage factor: Approx. 2.0.



The following model with the lead-wire cable code W1M3 is delivered with a vinyl-coated flat 3-wire cable 1 m long pre-attached.

KM-120-120-H2-11 W1M3

120×15×5

1 gage/ pkg

Patterns, Gage Resistance, Gage Factor	Models	Dimensions (mm)				Remarks
		Grid		Base		
		Length	Width	Length	Width	

●KMC Series Concrete-Embedded Strain Gages

The KMC series gages are designed to measure self-shrinkage and self-stress of cemented materials. They enable measurement of the self-shrinkage and high-fluidity concrete immediately after placing. They are also used effectively to check for cracks of cemented materials. Usually, a T-type thermocouple is installed near the gage, while the KMC series gages of H4 type do not require such the installation since they are equipped with a built-in thermocouple.

Uniaxial wire strain gages with vinyl-coated flat 3-wire cable 3 m long

Resistance: 120 Ω

Normal temperature to 70°C

1 gage/ pkg



The KMC series gages are available only with a vinyl-coated flat 3-wire cable 3 m long pre-attached.

KMC-70-120-H3

80×10×2

KMC-70-120-H4

80×10×2

T-type thermocouple built in