













Gage Terminals and Other Accessories



● **T-type Gage Terminals** A gage terminal is for connecting a strain gage and lead wires to protect the gage leads. It prevents the strain gage from receiving force and the gage leads from breaking or peeling off if the lead wires is pulled to some extent.

	Models	Dimensions (mm) (W x L x t)	Base Materials	Conductor Materials	Qty per Pack	Operating Temperature (°C)	Recommended Adhesives	Remarks
Foil types	 T-F2B NEW	5-pole 14x55x0.1 1-pole 14x11x0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120	CC-33A EP-34B	
	 T-F3B NEW	5-pole 14x65x0.1 1-pole 14x13x0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120	CC-33A EP-34B	For 3-wire system
	T-F13B NEW	5-pole 14x65x0.15 1-pole 14x13x0.15	Glass epoxy + double-coated adhesive tape			-30 to 50	Not required	Self-bonding
	 T-F7B NEW	5-pole 6x25x0.1 1-pole 6x5x0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120	CC-33A EP-34B	
	T-F17B NEW	5-pole 6x25x0.15 1-pole 6x5x0.15	Glass epoxy + double-coated adhesive tape			-30 to 50	Not required	Self-bonding
	 T-F8B NEW	5-pole 4x30x0.1 1-pole 4x6x0.1	Glass epoxy	Copper foil	20 sheets (5 poles/ sheet)	-196 to 120	CC-33A EP-34B	
	 T-F10B NEW	15x50x0.1	Glass epoxy	Copper foil	10 sheets	-196 to 120	CC-33A EP-34B	Mainly for 5-element gages
	 T-F23	5-pole 14x55x0.1 1-pole 14x11x0.1	Polyimide	Copper foil	20 sheets (5 poles/ sheet)	-196 to 200, -196 to 120 with CC-33A	CC-33A EP-34B	For high temperature
	T-F24	5-pole 9x40x0.1 1-pole 9x8x0.1						
	T-F25	5-pole 6x25x0.1 1-pole 6x5x0.1						
 T-F26	5-pole 14x55x0.1 1-pole 14x11x0.1	Polyimide	Copper foil	20 sheets (5 poles/ sheet)	-196 to 350	PI-32	For high temperature	
T-F27	5-pole 9x40x0.1 1-pole 9x8x0.1							
T-F28	5-pole 6x25x0.1 1-pole 6x5x0.1							
 T-F29 NEW	Outer: φ6 Inner: φ2.5	Glass epoxy	Copper foil	20 sheets	-196 to 120	EP-180, 340 CC-33A EP-34B	For measuring axial tension of bolts	
Mold types	 T-P1	14x10x4	Styrol	Tin-plated copper wire	20 PC.	-30 to 80	CC-33A	
	T-P4	14x10x4.5	Styrol + double-coated adhesive tape			-30 to 50	Not required	Self-bonding
	 T-P5	6x6x2	ABS	Tin-plated copper wire	20 PC.	-30 to 120	CC-33A	
	T-P6	6x6x2.5	ABS + double-coated adhesive tape			-30 to 50	Not required	Self-bonding
	 T-P7	15x10x4	ABS	Tin-plated copper wire	40 PC.	-30 to 80	CC-33A	For 3-wire system
	T-P8	15x10x4.5	ABS + double-coated adhesive tape			-30 to 50	Not required	Self-bonding
	 T-P9	6x5x4	Heat-resistant styrol	Tin-plated copper wire	40 PC.	-30 to 90	CC-33A	Rubber on the rear
	T-P10	6x5x6	Heat-resistant styrol + rubber					